



Rhein-Galerie, Ludwigshafen, Germany

## Essential info


Place / Country:	Ludwigshafen am Rhein, Germany
Year:	2010
Building type:	Shopping mall
Solutions:	CI System Ventilation Flap M CI System Glass Architecture KWS 60 Building automation / CI Control Technology Pneumatic upstroke opener (tandem drives) Heat insulation glazing
Efficiency:	32% energy saving Uw=1,3 W/(m <sup>2</sup> K) vs. Uw=1,9 W(m <sup>2</sup> K) as per German Energy Performance of Buildings Directive 2009

330 metres long, this two-storey shopping mall is provided with plenty of natural daylight thanks to several elliptic glass structures with a total surface of 2,900 m<sup>2</sup> along the length of its gallery. This results in lower power requirements for electric lighting, which, in turn, considerably reduces CO2 emissions into the environment.

- Integrated flap systems for SHEV function and natural ventilation; light transmission tested to EN 12207 (Class 4), watertightness as per EN 12208 (Class E1200), resistance under wind load as per EN 12210 (Class C4/B5)
- Thermally separated, extruded aluminium sections \_
- Conceptual design and installation of control devices \_
- Control process automation for SHEV and ventilation \_ functions
- Connected to building control technology via Modbus \_ connection



Rhein-Galerie, Ludwigshafen, Germany











## LAMILUX HEINRICH STRUNZ GMBH

Zehstraße 2 - Postfach 1540 - 95105 Rehau/aa - aaa+49/(0)92 83/5 95-0 - aaa+49/(0)92 83/5 95-29 0 aaaa information@lamilux.de - www.lamilux.de